



The **VW** floating pontoon is the natural product for protected and guarantees very high performance against corrosion. Its alloy frame of aluminum and the precious wooden trampling top make the Venice pontoon the most elegant choice for prestigious marina projects.

SPECIFICATIONS	VW01	VW02	VW03
Length (m)	12,00	10,00	8,00
Width (m)	2,45	2,45	2,45
Overload (kg/m <sup>2</sup> )	210	160	210
Displacement (ton)	334,00	300,00	337,00
Free board (cm)	65,00	63,00	65,00

#### FRAME

Completely aluminum alloy 6082T6 for nautical use, electrically soldered in an inert gas atmosphere. The particular design of the main profiles, allows for all mooring accessories to be positioned and fixed at any point of its length.

#### FLOATS

1. 40N/mm<sup>2</sup> reinforced cls floating units, expanded polystyrene inner core 15 kg/m<sup>3</sup>, stainless steel junction bolt.
2. waterproof polyethylene floating units, positioned as a catamaran ensuring high established pontoon, expanded polystyrene inner core, bolting stainless steel junction.

#### SERVICE CHANNELS

The pontoon is equipped with two 245x80 mm side compartments covered with anodized aluminum alloy covers.

#### JOINT SYSTEM

Flexible union with stainless steel tie rods and neoprene shock absorbers semi-rigid.

#### TRAMPLING PLANE

Offered with exotic wood slats or synthetic materials, fixing exclusively with screws in A4.

